

Wheeled foam dispenser station

Low pressure from 2 to 8 Bar



Wheeled
foam
dispenser
station
-
Mains water

16.7



TECHNICAL DETAILS

Wheeled foam dispenser station equipped with Foam Air System or Foam & Wash B.P. (By-Pass Foam/Rinsing)

- ✓ Stainless steel trolley
- ✓ Foam dispenser station Foam air system or Foam & Wash B.P. (By-Pass Foam/Rinsing)
- ✓ Antispot rear wheels Ø 100
- ✓ S/s pivoting rear wheels ø 100 with brake
- ✓ Stainless steel hose holder

AVAILABLE CONFIGURATION

CODE	FOAM DISPENSER STATION	HOSE	FLOW RATE (lt/h)	WATER PRESSURE (Bar)	WATER IN-LET MAX TEMPERATURE	PERCENTAGE OF ASPIRED PRODUCT (%)	WEIGHT (Kg)	DIMENSIONS LxHxD (mm)
30640	FOAM AIR SYSTEM	B.P. ½" mt. 20	~250	2 ~ 8	50 °C	0,1 ~ 10	25	580x1070x750
30642	F&W B.P. (BY-PASS)	B.P. ½" mt. 20	~250	2 ~ 8	50 °C	0,1 ~ 10	25	580x1070x750
Double Suction Version								
30640/2	FOAM AIR SYSTEM	B.P. ½" mt. 20	~250	2 ~ 8	50 °C	0,1 ~ 10	25	580x1070x750
30642/2	F&W B.P. (BY-PASS)	B.P. ½" mt. 20	~250	2 ~ 8	50 °C	0,1 ~ 10	25	580x1070x750