

VACUUM CLEANERS - DUST EXTRACTORS - HEAVY TOOLINGS

GS 3/78 OPT CYC

POWER MAX

WATER LIFT

AIRFLOW

TANK CAPACITY

 $3500 \text{ w} 2230 \quad 765 \text{ m}^3/\text{h} 78 \text{ l}$

 mmH_2O

EXCLUSIVE FEATURES

- **INNOVATIVE GASKET**
- **STRONG HOOKS**
- INDEPENDENT MOTORS WITH LIGHT SWITCHES
- **TIPPING TROLLEY**
- **MICROFIBER BAG**
- RELIABLE CONSTRUCTION **FOR INTENSIVE USE**
- **DETACHABLE TANK AND SOLID CART**
- **MULTI STAGE FILTRATION**
- **BIG AND BRAKED WHEELS**
- **ELECTROSTATIC DISSIPATION**



MOST FREQUENTLY USE

AGRICULTURE

INNOVATIONS





CONSTRUCTION

HARDWARE CUSTOMER

HEAVY INDUSTRY

SPECS



OPTIM TROLLEY IS EXTREMELY DURABLE AND MANEUVERABLE



CYCLONE SYSTEM



TIPPING TANK

TECHNICAL DATA

		GS 3/78 OPT CYC
Code		ASD015517
PERFORMANCE		
Usage		DRY
Motor		3
Power	W	3400-3500 max
Voltage	V	220-240
Water lift	mmH₂0	2230
Airflow	m³/h	765
Tank Capacity/Material	l	78/steel
Cable length	m	8,5
Filtering surface	cm²	2260
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	76
Diameter of accessories	mm	50
Dimensions (LxWxH)	mm	600x620x1335
Weight	kg	43

STANDARD EQUIPMENT

CODE: FTDP28843 **HEPA H13 CARTRIDGE** 2.260 cm²

CODE: -MICROFIBER BAG 12 I CODE: TBFX01139 **CONDUCTIVE FLEXIBLE** HOSE 5 m Ø50 mm







OPTIONAL ACCESSORIES

CODE: KTRI04795 **MICROFIBER BAG SET OF** 10 PCS









