

ST R





CA Wet&Dry 2 Motors: practical and professional wet and dry vacuum cleaners

The professional wet and dry 2-motor vacuum cleaners of the CA Wet&Dry range have been designed to provide practicality and professional results.

They are vacuum cleaners equipped with high capacity tanks but designed to be practical and easy to use. Resistant and easy to handle, they are used for the cleaning of medium surfaces or for the collection of solid material of various sizes, as well as liquids.

The versatility and performance of these professional vacuum cleaners make them suitable for cleaning companies, demanding applications and also for rental in Ho.Re.Ca., wellness & Sports, and public sectors. Dual motor models are the ideal solution for the removal of dust and liquids suction in the transport, logistics and large-scale distribution sectors.

KEY FACTORS OF THE CA WET&DRY 2 MOTORS RANGE:

- Available with polyethylene, polypropylene or stainless steel tanks.
- Optional front fixed accessory for easy liquids suction on large surfaces, available on demand.
- Possibility to choose versions with fixed or tilting trolley for a more practical emptying.
- Some models can be equipped with an optional quick drain kit to facilitate emptying operations.
- CA110.2 is equipped with a drain hose, accessory holder and a special opening for rinsing out the interior of the tank.
- Standard cloth filter.
- Standard sponge filter.
- Cartridge filter, washable cartridge filter, HEPA cartridge filter and nylon filter available as optional.
- Wide choice of available accessories that make the range of CA WET & DRY 2-motor vacuum cleaners extremely customizable.



CA 110.2 Tank capacity: 110 | Professional WET & DRY Suction: 2 motors

CA P58.3 WD Tank capacity: 77 l Professional WET & DR Suction: 2 motors

MODELS

CA P58.4 WDM Tank capacity: 77 I Professional WET & DRY Suction: 2 motors CA P58.4 WDB Tank capacity: 77 l Professional WET & DR\ Suction: 2 motors

CA A58.4 WDE

Tank capacity: 77 l Professional WET & DRN Suction: 2 motors

Details that matter



CA110.2 can be equipped with a front squeegee, controlled by a pedal placed at the rear of the unit, designed for quick and easy drying operations.

Thanks to their ergonomic handle these vacuum cleaners are easily transportable over all floors.

Fixed trolley versions are even easier to maneuver, while those with a tilting trolley are more practical to empty.

Models equipped with a TIP & POUR tilting trolley, allow the tank to be completely overturned while remaining on its hinge, making it very easy to empty.





CA110.2 is equipped with a standard drain hose, while for CA P58.4 WDM, CA P58.4 WBD and CA A58.4 WDB a quick drain kit is available as optional.

The convenient net bag of the CA110.2 incorporated onto the rear of the unit, can hold all accessories to keep them handy at all times.



The optimal tilt angle between the handle and the rear wheels allows CA110.2 to rest completely on the ground to favor a better emptying of the tank.











Available kits and accessories for the CA Wet&Dry 2 motors range



225439 KIT Ø 40 mm

405436 Cartridge filter

 \diamond

417432 Nylon filter

 \diamond





405430 Paper filter bag

0



405433 Washable Cartridge filter





204566 Front squeege CA P58.4 WDM CA P58.4 WDB CA A58.4 WDB 109918 109919 109925 0 0 0



443001 Microfiber filter bag

0



405434 HEPA cartridge filter

 \diamond



204641 Drain kit CA P58.4 WDM 109918

0



204577 Cloth filter

.

405429 Sponge filter

0



221157 Drain kit CA110.2 CA P58.4 WDB CA A58.4 WDB

109923 109919 109925 • 0 0

Legend

• standard 🛛 optional

| TECHNICAL DESCRIPTION | | CA110.2 | CA P58.3 WD | CA P58.4 WDM | CA P58.4 WDB | CA A58.4 WDM |
|-----------------------|---|-----------------------------|-----------------------------|-----------------------------|-----------------------------|--------------------------------|
| Voltage-Frequency | V-fase-Hz | 220/240-1-50/60 * | 220/240-1-50/60 * | 220/240-1-50/60 * | 220/240-1-50/60 * | 220/240-1-50/60 * |
| Power | W-Hp | 2200 | 2000 | 2200 | 2200 | 2200 |
| Motor | n./type | 2/Bypass double stage |
| Water lift | mmH ₂ O/inchH ₂ O | 2300/90,5 | 2100/82,6 | 2300/90,5 | 2300/90,5 | 2300/90,5 |
| Airflow | l/s / gal/s | 108 | 104 | 108 | 108 | 108 |
| Tank capacity | l/gal | 110 | 77 | 77 | 77 | 77 |
| Cable length | m/feet | 7 | 7 | 7 | 7 | 7 |
| Noise level | dB | 72 | 72 | 72 | 72 | 72 |
| Dimensions (Lxhxw) | mm/inch | 510x665x985 20x26,1x38,7 | 550x550x890 21,6x21,6x35 | 545x576x940 21,4x22,6x37 | 545x635x970 21,4x25x38,1 | 545x642x980 21,4x25,27x38,5 |
| Weight | Kg/lbs | 21/46,2 | 18.5/40,7 | 18.5/40,7 | 18.5/40,7 | 20/44 |
| | | | | | | |

*other voltages available on request



COMAC S.p.A. Via Maestri del Lavoro, 13 - 37059 Santa Maria di Zevio - Verona - ITALY Tel. 045 8774222 - www.comac.it - com@comac.it

Organisation certified by Q.C.B. Italia ISO 9001:2015, ISO 14001:2015, ISO 45001:2018



